



NORGREN Micro-fog lubricator EXCELON® series L72M

- Excelon design allows in-line or modular installation
- Flow sensor provides a nearly constant oil/air ratio over a wide range of flows
- All round [360°] visibility of sight-feed dome for ease of drip rate setting
- Micro-fog lubricators for best lubrication in general purpose pneumatic applications

Characteristics

Series: Excelon

Type: L72

Housing material: Zinc die-cast

Seal material: NBR

Drain type: None

Operating temperature: -34 / 65 °C

Reservoir capacity: 0.065 l

Port thread type	Port Size in	Bowl Material	Maximum operating pressure	Flow rate l/min	Article
BSPP [G]	1/4	Zinc	17	max. 24 l/s [G 1/4", 6.3 bar]	11584104
BSPP [G]	1/4	Polycarbonate	10		11584105
BSPP [G]	1/4	Polycarbonate	17		11584106
BSPP [G]	3/8	Zinc	17		11584107
BSPP [G]	3/8	Polycarbonate	10		11584108

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.