



SMC Lubricator series AL10-60-A

- Body sizes available: 10 ~ 60
- Thread type: M5, Rc(PT), NPT, G(PF)
- Port sizes: M5, 1/8, 1/4, 3/8, 1/2, 3/4, 1

Characteristics

Series: AL-A

Housing material: Zinc die-cast

Ambient temperature: -5 / 60 °C

Size	Port thread type	Port Size in	Bowl Material	Flow direction	Maximum operating pressure	Article
20	BSPP [G]	1/8	Polycarbonate	left ? right	10	12230862
20	BSPP [G]	1/4	Metal	left ? right	10	12735048
20	BSPP [G]	1/4	Polycarbonate	left ? right	10	12735050
30	BSPP [G]	1/4	Polycarbonate	left ? right	10	11885756
30	BSPP [G]	3/8	Metal	left ? right	10	12735051
30	BSPP [G]	3/8	Metal	left ? right	10	12735052
30	BSPP [G]	3/8	Polycarbonate	left ? right	10	12230869
40	BSPP [G]	1/4	Polycarbonate	left ? right	10	12230882
40	BSPP [G]	3/8	Polycarbonate	left ? right	10	12552759
40	BSPP [G]	1/2	Metal	left ? right	10	12735053
40	BSPP [G]	1/2	Metal	left ? right	10	12230887
40	BSPP [G]	1/2	Polycarbonate	left ? right	10	24114946
40	BSPP [G]	1/2	Polycarbonate	left ? right	10	12735054
40	BSPP [G]	3/4	Polycarbonate	left ? right	10	12230881
40	NPT	1/2	Polycarbonate	left ? right	10	12735055

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.