



SMC Air Filter + Regulator + Lubricator, series AC10-40-A

- Filter + Regulator + Lubricator.
- Body size: 10, 20, 25, 30, 40.
- Port Size: M5, 1/8, 1/4, 3/8, 1/2, 3/4.
- Max. operating pressure: 1.0 MPa.
- Attachments.

Characteristics

Series: AC-A
Function: Filter-Regulator-Lubricator
Bowl Material: Polycarbonate
Lockable: No
Operating temperature: -5 / 60 °C

Size	Port thread type	Port Size	Filtration level	With pressure gauge	Drain type	Flow direction	Self-venting	Adjustment range	Article
		in	µm						
20	BSPP [G]	1/4	5	No	Automatic	left ? right	Yes	0.05 - 0.7 Mpa	12230665
30	BSPP [G]	3/8	5	No	Automatic	left ? right	Yes	0.05 - 0.7 Mpa	12230678
30	BSPP [G]	3/8	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230677
40	BSPP [G]	3/8	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12552750
40	BSPP [G]	3/4	5	Yes	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230698

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.