



SMC Filter Regulator + Lubricator, series AC10A-40A-A

- Filter Regulator + Lubricator.
- Body size: 10, 20, 30, 40.
- Port Size: M5, 1/8, 1/4, 3/8, 1/2, 3/4.
- Max. operating pressure: 1.0 MPa.
- Attachments.

Characteristics

Series: AC-A

Function: Filter-Regulator-Lubricator

Bowl Material: Polycarbonate

Lockable: No

Operating temperature: -5 / 60 °C

Size	Port thread type	Port Size	Filtration level	With pressure gauge	Drain type	Flow direction	Self-venting	Adjustment range	Article
		in	µm						
20	BSPP [G]	1/8	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230657
30	BSPP [G]	1/4	5	No	Automatic	left ? right	Yes	0.05 - 0.7 Mpa	12230669
20	BSPP [G]	1/4	5	No	Automatic	left ? right	Yes	0.05 - 0.7 Mpa	12230660
30	BSPP [G]	1/4	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12235670
20	BSPP [G]	1/4	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	11884848
20	BSPP [G]	1/4	5	Yes	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12937073
30	BSPP [G]	3/8	5	No	Automatic	left ? right	Yes	0.05 - 0.7 Mpa	12230670
30	BSPP [G]	3/8	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	11884849
30	BSPP [G]	3/8	5	Yes	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230672
40	BSPP [G]	1/2	5	No	Automatic	left ? right	Yes	0.05 - 0.7 Mpa	12230684
40	BSPP [G]	1/2	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	11884850
40	BSPP [G]	1/2	5	Yes	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230688
40	BSPP [G]	3/4	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230689
40	BSPP [G]	3/4	5	Yes	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230691

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.