



NORGREN Electropneumatically operated Olympian Plus P64F Soft-start valve

- Assists machine designers in complying with the European Machinery Directive
- Can help existing machinery to comply with PUWER (Provision and Use of Work Equipment Regulations)
- Controlled increase of downstream pressure on start up
- High forward flow capacity
- High flow dump facility

Characteristics

Series: Olympian Plus

Type: P64F

Housing material: Zinc alloy

Seal material: Nitrile rubber

Manufacturer ID	Connection	Port Size in	Operating pressure bar	Article
P64F-NNC-PFN			3 / 10	11586284
P64F-3GC-PFN	BSPP(G)	3/8	3 / 10	11586272
P64F-4GC-PFA	BSPP(G)	1/2	3 / 10	11586276
P64F-4GC-PFN	BSPP(G)	1/2	3 / 10	11586277
P64F-6GC-PFN	BSPP(G)	3/4	3 / 10	11586279
P64F-6GC-PFA	BSPP(G)	3/4	3 / 10	11586278

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.