

NORGREN Series X3 04 manually operated 5/2 slide valve



- Wide range of operators
- Suitable for multi-directional flow and dual supply applications
- High flow capacity
- Lightweight corrosion resistant materials

Characteristics

Series: Super X

Operation: Mechanical

Operating temperature: 0 / 70 °C

Material cover: Nylon, glas filled

Fluid: Compressed air

Port thread type	Port Size in	Operating pressure bar	Function	Colour push button	Housing material	Article
BSPP (G)	1/8		5/2	Red		11575039
BSPP (G)	1/8		5/2	Green		11575045
BSPP (G)	1/8	0 / 10	5/2		Zinc	11575056
BSPP (G)	1/8	0 / 10	5/2		Zinc	11575059
BSPP (G)	1/8		5/2			11575043
BSPP (G)	1/8		5/2	Red		11575046
BSPP (G)	1/8		5/2			11575040
BSPP (G)	1/8	0 / 10	5/2	Black	Zinc	11575050
BSPP (G)	1/8		5/2	Black		11575041
BSPP (G)	1/8		5/2	Green		11575038
BSPP (G)	1/8		5/2	Red		11575049
BSPP (G)	1/8	0 / 10	5/2	Black	Zinc	11575037
BSPP (G)	1/8	0 / 10	5/2		Zinc	11575057
BSPP (G)	1/8	0 / 10	5/2		Zinc	11575047
BSPP (G)	1/8		5/2	Black		11575044
BSPP (G)	1/8	0 / 10	5/2		Zinc	11575058
BSPP (G)	1/8	0 / 10	5/2		Zinc	11575036
BSPP (G)	1/8	0 / 10	5/2	Black	Zinc	11575051
BSPP (G)	1/8		5/2			11575033

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.