



## AVENTICS Maintenance unit 2-part Series NL2-ACD

### Characteristics

**Series:** NL2-ACD

**Function:** Filter-Regulator-Lubricator

**Bowl Material:** Zinc die-cast

**Operating temperature:** -10 / 60 °C

**Material seal:** NBR

**Filter element material:** Polyethylene

**Housing material:** Zinc die-cast

| Port thread type | Port Size | Filtration level | With pressure gauge | Drain type     | Self-venting | Maximum operating pressure | Adjustment range | Flow rate | Weight | Article  |
|------------------|-----------|------------------|---------------------|----------------|--------------|----------------------------|------------------|-----------|--------|----------|
|                  | in        | µm               |                     |                |              |                            |                  | l/min     | g      |          |
| BSPP [G]         | 1/4       | 5                | Yes                 | Semi automatic | Yes          | 16                         | 0.5 - 10 bar     | 1100      | 850    | 12129840 |
| BSPP [G]         | 1/4       | 5                | Yes                 | Semi automatic | Yes          | 16                         | 0.5 - 10 bar     | 1100      | 1200   | 11303170 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.