

STAUFF Push-to-connect coupling with poppet valve series HP



Push/Pull Push-to-Connect Couplings with poppet Valve of the HP Series consist of a male tip and a female body which are used for quick and easy connection (push) and disconnection of tubes, pipes and hoses by hand, i.e. without tools.

The Series was developed according to ISO 7241-1 A and ISO 5675 (for selected sizes) in the following nominal sizes 06, 10, 12, 19, [1/4" -1"] and can be connected under pressure with male tips of the HU series. The HU series consists of a male tip designed according to ISO 7241-1 A and is compatible with female bodys of this type.

Characteristics

Series: HP

Material: Steel

Surface protection: Zinc-Nickel

Valve shape: Poppet valve

Minimum medium temperature (continuous): -25 °C

Maximum medium temperature (continuous): 100 °C

Standard: ISO 7241-1A

Connectable under residual pressure: No

Execution

- The sleeve of the female body can be installed in a bulkhead with retaining rings. In this way, the female body fulfils the function of a breakaway coupling. Should a male tip be torn away from a female body installed in this way, the system is decoupled and the valves close automatically, thus preventing damage to the hose and possible loss of oil.

Application

- Agricultural and forestry machinery

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	11489315
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	250	0.8	20	NBR/PTFE	13866071
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	250	0.8	20	NBR/PTFE	13866072
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	250	0.8	20	NBR/PTFE	13866069
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" NPT	250	0.8	20	NBR/PTFE	13866070
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	250	1.2	40	NBR/PTFE	13866085
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	250	1.2	40	NBR/PTFE	13866088
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	250	1.2	40	NBR/PTFE	14508459
Coupling (female)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	250	1.2	40	NBR/PTFE	13866091
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR/PTFE	13866086
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR/PTFE	13866089
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR/PTFE	14508461
Coupling (female)	2	10	3/8"	Cutting ring connection	10S - M18x1.5	250	1.2	40	NBR/PTFE	13866092
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	250	1.2	40	NBR/PTFE	13866087
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	250	1.2	40	NBR/PTFE	14508464
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	250	1.2	40	NBR/PTFE	13866093
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	250	1.2	40	NBR/PTFE	13866095

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article Max. 200 articles in the table
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	250	1.2	40	NBR/PTFE	14508465
Coupling (female)	2	10	3/8"	External thread	3/8" BSP cyl.	250	1.2	40	NBR/PTFE	13866080
Coupling (female)	2	10	3/8"	Internal thread	1/4" BSP cyl.	250	1.2	40	NBR/PTFE	13866081
Coupling (female)	2	10	3/8"	Internal thread	3/8" BSP cyl.	250	1.2	40	NBR/PTFE	13866082
Coupling (female)	2	10	3/8"	Internal thread	3/8" BSP cyl.	250	1.2	40	NBR/PTFE	13866114
Coupling (female)	2	10	3/8"	Internal thread	3/8" NPT	250	1.2	40	NBR/PTFE	13866084
Coupling (female)	2	10	3/8"	Internal thread	M 16x1.5	250	1.2	40	NBR/PTFE	13866083
Coupling (female)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	250	8	120	NBR/PTFE	13866188
Coupling (female)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	250	8	120	NBR/PTFE	13866191
Coupling (female)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	250	8	120	NBR/PTFE	14230092
Coupling (female)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	250	8	120	NBR/PTFE	13866193
Coupling (female)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	250	8	120	NBR/PTFE	13866195
Coupling (female)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	250	8	120	NBR/PTFE	14230093
Coupling (female)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	250	8	120	NBR/PTFE	14230094
Coupling (female)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	250	8	120	NBR/PTFE	13866194
Coupling (female)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	250	8	120	NBR/PTFE	14230095
Coupling (female)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	250	8	120	NBR/PTFE	13866190
Coupling (female)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	250	8	120	NBR/PTFE	13866192
Coupling (female)	4	19	3/4"	Internal thread	3/4" BSP cyl.	250	8	120	NBR/PTFE	13866185
Coupling (female)	4	19	3/4"	Internal thread	3/4" NPT	250	8	120	NBR/PTFE	13866187
Coupling (female)	4	19	3/4"	Internal thread	M 22x1.5	250	8	120	NBR/PTFE	13866186
Coupling (female)	6	25	1"	Cutting ring connection	15L - M22x1.5	250	12	160	NBR/PTFE	13866216
Coupling (female)	6	25	1"	Cutting ring connection	18L - M26x1.5	250	12	160	NBR/PTFE	13866212
Coupling (female)	6	25	1"	Cutting ring connection	18L - M26x1.5	250	12	160	NBR/PTFE	13866217
Coupling (female)	6	25	1"	Cutting ring connection	20S - M30x2.0	250	12	160	NBR/PTFE	14230099
Coupling (female)	6	25	1"	Cutting ring connection	20S - M30x2.0	250	12	160	NBR/PTFE	13866221
Coupling (female)	6	25	1"	Cutting ring connection	22L - M30x2.0	250	12	160	NBR/PTFE	13866213
Coupling (female)	6	25	1"	Cutting ring connection	22L - M30x2.0	250	12	160	NBR/PTFE	13866218
Coupling (female)	6	25	1"	Cutting ring connection	25S - M36x2.0	250	12	160	NBR/PTFE	14230100
Coupling (female)	6	25	1"	Cutting ring connection	25S - M36x2.0	250	12	160	NBR/PTFE	14230101
Coupling (female)	6	25	1"	Cutting ring connection	28L - M36x2.0	250	12	160	NBR/PTFE	13866214
Coupling (female)	6	25	1"	Cutting ring connection	28L - M36x2.0	250	12	160	NBR/PTFE	13866219
Coupling (female)	6	25	1"	Cutting ring connection	30S - M42x2.0	250	12	160	NBR/PTFE	13866220
Coupling (female)	6	25	1"	Cutting ring connection	30S - M42x2.0	250	12	160	NBR/PTFE	13866222

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Coupling (female)	6	25	1"	Internal thread	1" BSP cyl.	250	12	160	NBR/PTFE	13866210
Coupling (female)	6	25	1"	Internal thread	1" NPT	250	12	160	NBR/PTFE	13866211
Coupling (female)	6	25	1"	Internal thread	3/4" BSP cyl.	250	12	160	NBR/PTFE	11459937
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	250	0.8	20	NBR	13866075
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	250	0.8	20	NBR	13866076
Plug (male)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	250	0.8	20	NBR	13866073
Plug (male)	1	6.3	1/4"	Internal thread	1/4" NPT	250	0.8	20	NBR	13866074
Plug (male)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	250	1.2	40	NBR	13866102
Plug (male)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	250	1.2	40	NBR	13866105
Plug (male)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	250	1.2	40	NBR	13866108
Plug (male)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	250	1.2	40	NBR	14508471
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR	13866103
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR	13866106
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR	14508473
Plug (male)	2	10	3/8"	Cutting ring connection	10S - M18x1.5	250	1.2	40	NBR	13866109
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	250	1.2	40	NBR	13866104
Plug (male)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	250	1.2	40	NBR	13866110
Plug (male)	2	10	3/8"	External thread	3/8" BSP cyl.	250	1.2	40	NBR	13866097
Plug (male)	2	10	3/8"	Internal thread	1/4" BSP cyl.	250	1.2	40	NBR	13866099
Plug (male)	2	10	3/8"	Internal thread	3/8" BSP cyl.	250	1.2	40	NBR	13866100
Plug (male)	2	10	3/8"	Internal thread	3/8" BSP cyl.	250	1.2	40	NBR	13866116
Plug (male)	2	10	3/8"	Internal thread	3/8" NPT	250	1.2	40	NBR	13866101
Plug (male)	2	10	3/8"	Internal thread	M 16x1.5	250	1.2	40	NBR	14230056
Plug (male)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	250	8	120	NBR	13866199
Plug (male)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	250	8	120	NBR	13866202
Plug (male)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	250	8	120	NBR	13866200
Plug (male)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	250	8	120	NBR	13866203
Plug (male)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	250	8	120	NBR	14230096
Plug (male)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	250	8	120	NBR	13866206
Plug (male)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	250	8	120	NBR	13866201
Plug (male)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	250	8	120	NBR	14230097
Plug (male)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	250	8	120	NBR	13866205
Plug (male)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	250	8	120	NBR	14230098
Plug (male)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	250	8	120	NBR	11540485

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure	Spillage	Max. flow rate	Sealing	Article
		mm				bar	ml	l/min		Max. 200 articles in the table
Plug (male)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	250	8	120	NBR	13866204
Plug (male)	4	19	3/4"	Internal thread	3/4" BSP cyl.	250	8	120	NBR	13866196
Plug (male)	4	19	3/4"	Internal thread	3/4" NPT	250	8	120	NBR	13866198
Plug (male)	4	19	3/4"	Internal thread	M 22x1.5	250	8	120	NBR	13866197
Plug (male)	6	25	1"	Cutting ring connection	18L - M26x1.5	250	12	160	NBR	13866226
Plug (male)	6	25	1"	Cutting ring connection	18L - M26x1.5	250	12	160	NBR	13866230
Plug (male)	6	25	1"	Cutting ring connection	20S - M30x2.0	250	12	160	NBR	13866233
Plug (male)	6	25	1"	Cutting ring connection	20S - M30x2.0	250	12	160	NBR	13866236
Plug (male)	6	25	1"	Cutting ring connection	22L - M30x2.0	250	12	160	NBR	13866227
Plug (male)	6	25	1"	Cutting ring connection	22L - M30x2.0	250	12	160	NBR	13866231
Plug (male)	6	25	1"	Cutting ring connection	25S - M36x2.0	250	12	160	NBR	13866234
Plug (male)	6	25	1"	Cutting ring connection	25S - M36x2.0	250	12	160	NBR	14230102
Plug (male)	6	25	1"	Cutting ring connection	28L - M36x2.0	250	12	160	NBR	13866228
Plug (male)	6	25	1"	Cutting ring connection	28L - M36x2.0	250	12	160	NBR	13866232
Plug (male)	6	25	1"	Cutting ring connection	30S - M42x2.0	250	12	160	NBR	13866235
Plug (male)	6	25	1"	Cutting ring connection	30S - M42x2.0	250	12	160	NBR	14230103
Plug (male)	6	25	1"	Internal thread	1" BSP cyl.	250	12	160	NBR	13866224
Plug (male)	6	25	1"	Internal thread	1" NPT	250	12	160	NBR	13866225
Plug (male)	6	25	1"	Internal thread	3/4" BSP cyl.	250	12	160	NBR	11459938
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR/PTFE	14508462
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR/PTFE	14508460
Coupling (female)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	250	1.7	100	NBR	14230057
Coupling (female)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	250	1.7	100	NBR	14508490
Coupling (female)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	250	1.7	100	NBR	14230058
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	250	1.7	100	NBR	11489319
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	250	1.7	100	NBR	13866137
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	250	1.7	100	NBR	14508491
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	NBR	14230059
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	NBR	14230060
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	NBR	14508493
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	No sealing	14508495
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	FKM	13866147
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	14508496
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	14230264

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure	Spillage	Max. flow rate	Sealing	Article
		mm				bar	ml	l/min		Max. 200 articles in the table
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	11489314
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	11540732
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	14508497
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	14230265
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	250	1.7	100	NBR	13866141
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	250	1.7	100	NBR	13866143
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	250	1.7	100	NBR	14508499
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	250	1.7	100	NBR	14508500
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	250	1.7	100	NBR	14230061
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	250	1.7	100	NBR	14508501
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	250	1.7	100	NBR	14230062
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	FKM	14508503
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	NBR	13866134
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	NBR	13866138
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	NBR	14508502
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	NBR	14230266
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	FKM	13866182
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	NBR	13866142
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	NBR	14230063
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	NBR	14508504
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	250	1.7	100	NBR	13866135
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	250	1.7	100	NBR	14508505
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	250	1.7	100	NBR	14250750
Coupling (female)	3	12.5	1/2"	External thread	1/2" BSP cyl.	250	1.7	100	NBR	13866123
Coupling (female)	3	12.5	1/2"	External thread	3/8" BSP cyl.	250	1.7	100	NBR	14230064
Coupling (female)	3	12.5	1/2"	External thread	3/8" BSP cyl.	250	1.7	100	NBR	14230065
Coupling (female)	3	12.5	1/2"	External thread	M 20x1.5	250	1.7	100	NBR	14508520
Coupling (female)	3	12.5	1/2"	External thread	M 22x1.5	250	1.7	100	FKM	14508522
Coupling (female)	3	12.5	1/2"	External thread	M 22x1.5	250	1.7	100	NBR	14230070
Coupling (female)	3	12.5	1/2"	External thread	M 22x1.5 OR	250	1.7	100	NBR	14508521
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	250	1.7	100	FKM	13866146
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	250	1.7	100	NBR	14230267
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	250	1.7	100	NBR	13866126
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" NPT	250	1.7	100	NBR	14230071

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Coupling (female)	3	12.5	1/2"	Internal thread	3/4-16 UNF	250	1.7	100	NBR	14230072
Coupling (female)	3	12.5	1/2"	Internal thread	3/8" BSP cyl.	250	1.7	100	FKM	14508518
Coupling (female)	3	12.5	1/2"	Internal thread	3/8" BSP cyl.	250	1.7	100	NBR	11489311
Coupling (female)	3	12.5	1/2"	Internal thread	M 16x1.5 OR	250	1.7	100	NBR	14230066
Coupling (female)	3	12.5	1/2"	Internal thread	M 18x1.5 OR	250	1.7	100	NBR	14230067
Coupling (female)	3	12.5	1/2"	Internal thread	M 20x1.5 OR	250	1.7	100	NBR	14230068
Coupling (female)	3	12.5	1/2"	Internal thread	M 22x1.5	250	1.7	100	NBR	14230069
Coupling (female)	3	12.5	1/2"	Internal thread	M 22x1.5	250	1.7	100	NBR	14230268
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR	14508474
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	250	1.2	40	NBR	14508472
Plug (male)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	250	1.7	100	NBR	14230073
Plug (male)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	250	1.7	100	NBR	14230074
Plug (male)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	250	1.7	100	NBR	14508533
Plug (male)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	250	1.7	100	NBR	11489318
Plug (male)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	250	1.7	100	NBR	14508534
Plug (male)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	250	1.7	100	NBR	14230075
Plug (male)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	NBR	14230076
Plug (male)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	NBR	14230077
Plug (male)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	250	1.7	100	NBR	14508536
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	FKM	13866176
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	13866159
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	250	1.7	100	NBR	14230078
Plug (male)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	250	1.7	100	NBR	13866167
Plug (male)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	250	1.7	100	NBR	13866171
Plug (male)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	250	1.7	100	NBR	14230079
Plug (male)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	250	1.7	100	NBR	14230080
Plug (male)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	NBR	13866160
Plug (male)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	250	1.7	100	NBR	14081344
Plug (male)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	FKM	13866183
Plug (male)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	NBR	13866169
Plug (male)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	250	1.7	100	NBR	14230081
Plug (male)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	250	1.7	100	NBR	13866161
Plug (male)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	250	1.7	100	NBR	14230082
Plug (male)	3	12.5	1/2"	External thread	1/2" BSP cyl.	250	1.7	100	NBR	13866151

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Plug (male)	3	12.5	1/2"	External thread	3/8" BSP cyl.	250	1.7	100	NBR	13866150
Plug (male)	3	12.5	1/2"	External thread	M 16x1.5	250	1.7	100	NBR	14230084
Plug (male)	3	12.5	1/2"	External thread	M 22x1.5	250	1.7	100	NBR	14230087
Plug (male)	3	12.5	1/2"	External thread	M 22x1.5 OR	250	1.7	100	NBR	14230088
Plug (male)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	250	1.7	100	NBR	11459953
Plug (male)	3	12.5	1/2"	Internal thread	1/2" NPT	250	1.7	100	NBR	14230090
Plug (male)	3	12.5	1/2"	Internal thread	3/4-16 UNF	250	1.7	100	NBR	14230091
Plug (male)	3	12.5	1/2"	Internal thread	3/8" BSP cyl.	250	1.7	100	NBR	11489322
Plug (male)	3	12.5	1/2"	Internal thread	M 12x1.5 OR	250	1.7	100	NBR	14230083
Plug (male)	3	12.5	1/2"	Internal thread	M 16x1.5 OR	250	1.7	100	NBR	14230085
Plug (male)	3	12.5	1/2"	Internal thread	M 18x1.5 OR	250	1.7	100	NBR	14230086
Plug (male)	3	12.5	1/2"	Internal thread	M 22x1.5 OR	250	1.7	100	NBR	14230089

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.