

STAUFF Screw-to-connect coupling with poppet valve series HS



Screw-to-connect couplings of the HS Series consist of a female body with external thread and a male tip with a screw sleeve. The Series is developed for particularly heavy-duty applications for connecting hydraulic lines up to DN38 [1-1/2"].

Coupling (screwing) and uncoupling (unscrewing) of the two halves is safe and very easy. The coupling is designed to open both valves when connected together and due to their rugged design, higher operating and burst pressures, they are well suited for heavy-duty service conditions in construction machinery.

The Series was developed according to ISO 14541 [BG 1-6] in the following nominal sizes 06, 10, 12, 16, 19, 25, 38 [1/4" - 1-1/2"].

Characteristics

Series: HS

Material: Steel

Surface protection: Zinc-Nickel

Valve shape: Poppet valve

Minimum medium temperature (continuous): -25 °C

Maximum medium temperature (continuous): 100 °C

Standard: ISO 14541

Connectable under residual pressure: Yes, with restrictions

Application

- Construction machinery

Technical Information

Connect under pressure:

- male tip/female body up to 33% of the working pressure with tools

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	450	0.8	20	NBR/PTFE	14230104
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	450	0.8	20	NBR/PTFE	13866519
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8S - M16x1.5	450	0.8	20	NBR/PTFE	13866521
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	450	0.8	20	NBR/PTFE	13866516
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" NPT	450	0.8	20	NBR/PTFE	13866518
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	450	1.3	40	NBR/PTFE	13866537
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	450	1.3	40	NBR/PTFE	14230105
Coupling (female)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	450	1.3	40	NBR/PTFE	13866541
Coupling (female)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	450	1.3	40	NBR/PTFE	14508713
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	450	1.3	40	NBR/PTFE	13866538
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	450	1.3	40	NBR/PTFE	13866540
Coupling (female)	2	10	3/8"	Cutting ring connection	10S - M18x1.5	450	1.3	40	NBR/PTFE	13866542
Coupling (female)	2	10	3/8"	Cutting ring connection	10S - M18x1.5	450	1.3	40	NBR/PTFE	14034038
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	450	1.3	40	NBR/PTFE	14508717
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	450	1.3	40	NBR/PTFE	14508716
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	450	1.3	40	NBR/PTFE	13866543
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	450	1.3	40	NBR/PTFE	14508718

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure	Spillage	Max. flow rate	Sealing	Article
		mm				bar	ml	l/min		Max. 200 articles in the table
Coupling (female)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	450	1.3	40	NBR/PTFE	14508719
Coupling (female)	2	10	3/8"	External thread	3/4"-16 UNF [JIC]	450	1.3	40	NBR/PTFE	14508721
Coupling (female)	2	10	3/8"	External thread	3/8" BSP cyl.	450	1.3	40	NBR/PTFE	13866533
Coupling (female)	2	10	3/8"	External thread	11/16"-16 UN [ORFS]	450	1.3	40	NBR/PTFE	14508723
Coupling (female)	2	10	3/8"	Internal thread	1/4" BSP cyl.	450	1.3	40	NBR/PTFE	13866534
Coupling (female)	2	10	3/8"	Internal thread	3/8" BSP cyl.	450	1.3	40	NBR/PTFE	1019192
Coupling (female)	2	10	3/8"	Internal thread	3/8" NPT	450	1.3	40	NBR/PTFE	13866536
Coupling (female)	2	10	3/8"	Internal thread	M 16x1.5	450	1.3	40	NBR/PTFE	13866535
Coupling (female)	2	10	3/8"	Internal thread	M 16x1.5 WD	450	1.3	40	NBR/PTFE	14508722
Coupling (female)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	400	3.1	80	NBR/PTFE	14230115
Coupling (female)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	400	3.1	80	NBR/PTFE	14508741
Coupling (female)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	400	3.1	80	NBR/PTFE	13866574
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	400	3.1	80	NBR/PTFE	13866570
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	400	3.1	80	NBR/PTFE	13866575
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	400	3.1	80	NBR/PTFE	14508742
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	400	3.1	80	NBR/PTFE	13866579
Coupling (female)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	400	3.1	80	NBR/PTFE	13866583
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	400	3.1	80	NBR/PTFE	13866571
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	400	3.1	80	NBR/PTFE	13866576
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	400	3.1	80	NBR/PTFE	14508743
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	400	3.1	80	NBR/PTFE	13866580
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	400	3.1	80	NBR/PTFE	13866584
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	400	3.1	80	NBR/PTFE	14508744
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	400	3.1	80	FKM/PTFE	14508746
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	400	3.1	80	NBR/PTFE	13866581
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	400	3.1	80	NBR/PTFE	14508745
Coupling (female)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	400	3.1	80	NBR/PTFE	14230116
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	400	3.1	80	NBR/PTFE	13866572
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	400	3.1	80	NBR/PTFE	13866577
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	400	3.1	80	NBR/PTFE	14508747
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	400	3.1	80	NBR/PTFE	13866582
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	400	3.1	80	NBR/PTFE	13866585
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	400	3.1	80	NBR/PTFE	14508748
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	400	3.1	80	NBR/PTFE	13866573

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	400	3.1	80	NBR/PTFE	13866578
Coupling (female)	3	12.5	1/2"	External thread	1/2" BSP cyl.	400	3.1	80	NBR/PTFE	13866564
Coupling (female)	3	12.5	1/2"	External thread	3/8" BSP cyl.	400	3.1	80	NBR/PTFE	13866563
Coupling (female)	3	12.5	1/2"	External thread	M 22x1.5	400	3.1	80	NBR/PTFE	13866565
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	400	3.1	80	NBR/PTFE	1019194
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" NPT	400	3.1	80	NBR/PTFE	13866569
Coupling (female)	3	12.5	1/2"	Internal thread	3/8" BSP cyl.	400	3.1	80	NBR/PTFE	13866566
Coupling (female)	3	12.5	1/2"	Internal thread	M 18x1.5 OR	400	3.1	80	NBR/PTFE	13866567
Coupling (female)	3	12.5	1/2"	Internal thread	M 22x1.5 OR	400	3.1	80	NBR/PTFE	13866568
Coupling (female)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	400	5.6	120	NBR/PTFE	14230120
Coupling (female)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	400	5.6	120	NBR/PTFE	13866618
Coupling (female)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	400	5.6	120	NBR/PTFE	13866615
Coupling (female)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	400	5.6	120	NBR/PTFE	13866619
Coupling (female)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	400	5.6	120	NBR/PTFE	13903238
Coupling (female)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	400	5.6	120	NBR/PTFE	13866624
Coupling (female)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	400	5.6	120	NBR/PTFE	13866616
Coupling (female)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	400	5.6	120	NBR/PTFE	13866620
Coupling (female)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	400	5.6	120	NBR/PTFE	13866623
Coupling (female)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	400	5.6	120	NBR/PTFE	13866625
Coupling (female)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	400	5.6	120	NBR/PTFE	13866617
Coupling (female)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	400	5.6	120	NBR/PTFE	13866621
Coupling (female)	4	19	3/4"	Internal thread	1/2" BSP cyl.	400	5.6	120	NBR/PTFE	13866612
Coupling (female)	4	19	3/4"	Internal thread	3/4" NPT	400	5.6	120	NBR/PTFE	13866614
Coupling (female)	4	19	3/4"	Internal thread	M 22x1.5	400	5.6	120	NBR/PTFE	13866613
Coupling (female)	6	19	3/4"	Internal thread	3/4" BSP cyl.	400	5.6	120	NBR/PTFE	1065479
Coupling (female)	6	25	1"	Cutting ring connection	18L - M26x1.5	300	12.3	160	NBR/PTFE	11330657
Coupling (female)	6	25	1"	Cutting ring connection	18L - M26x1.5	300	12.3	160	NBR/PTFE	13866652
Coupling (female)	6	25	1"	Cutting ring connection	20S - M30x2.0	300	12.3	160	NBR/PTFE	13866655
Coupling (female)	6	25	1"	Cutting ring connection	20S - M30x2.0	300	12.3	160	NBR/PTFE	13866659
Coupling (female)	6	25	1"	Cutting ring connection	22L - M30x2.0	300	12.3	160	NBR/PTFE	13866648
Coupling (female)	6	25	1"	Cutting ring connection	22L - M30x2.0	300	12.3	160	NBR/PTFE	13866653
Coupling (female)	6	25	1"	Cutting ring connection	25S - M36x2.0	300	12.3	160	NBR/PTFE	13866656
Coupling (female)	6	25	1"	Cutting ring connection	25S - M36x2.0	300	12.3	160	NBR/PTFE	1032652
Coupling (female)	6	25	1"	Cutting ring connection	28L - M36x2.0	300	12.3	160	NBR/PTFE	13866649

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Coupling (female)	6	25	1"	Cutting ring connection	28L - M36x2.0	300	12.3	160	NBR/PTFE	13866654
Coupling (female)	6	25	1"	Cutting ring connection	30S - M42x2.0	300	12.3	160	NBR/PTFE	13866657
Coupling (female)	6	25	1"	Cutting ring connection	30S - M42x2.0	300	12.3	160	NBR/PTFE	13866660
Coupling (female)	6	25	1"	Cutting ring connection	35L - M45x2.0	300	12.3	160	NBR/PTFE	13866650
Coupling (female)	6	25	1"	Cutting ring connection	38S - M52x2.0	300	12.3	160	NBR/PTFE	13866658
Coupling (female)	6	25	1"	Cutting ring connection	38S - M52x2.0	300	12.3	160	NBR/PTFE	13866661
Coupling (female)	6	25	1"	Internal thread	1" BSP cyl.	300	12.3	160	NBR/PTFE	1019196
Coupling (female)	6	25	1"	Internal thread	1" NPT	300	12.3	160	NBR/PTFE	13866647
Coupling (female)	6	25	1"	Internal thread	3/4" BSP cyl.	300	12.3	160	NBR/PTFE	1019195
Coupling (female)	6	25	1"	SAE flange	SAE 6000 psi 1"	300	12.3	160	NBR/PTFE	14230127
Coupling (female)	6	25	1"	SAE flange	SAE 6000 psi 3/4"	300	12.3	160	NBR/PTFE	14230126
Coupling (female)	8	38	1.1/2"	Cutting ring connection	30S - M42x2.0	350	52.3	220	NBR/PTFE	13866688
Coupling (female)	8	38	1.1/2"	Cutting ring connection	30S - M42x2.0	350	52.3	220	NBR/PTFE	14230131
Coupling (female)	8	38	1.1/2"	Cutting ring connection	35L - M45x2.0	350	52.3	220	NBR/PTFE	13866686
Coupling (female)	8	38	1.1/2"	Cutting ring connection	38S - M52x2.0	350	52.3	220	NBR/PTFE	13866689
Coupling (female)	8	38	1.1/2"	Cutting ring connection	38S - M52x2.0	350	52.3	220	NBR/PTFE	13866690
Coupling (female)	8	38	1.1/2"	Internal thread	1.1/2" BSP cyl.	350	52.3	220	NBR/PTFE	13866684
Coupling (female)	8	38	1.1/2"	Internal thread	1.1/4" BSP cyl.	350	52.3	220	NBR/PTFE	13866683
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	450	0.8	20	NBR	13866525
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	450	0.8	20	NBR	13866526
Plug (male)	1	6.3	1/4"	Cutting ring connection	8S - M16x1.5	450	0.8	20	NBR	13866527
Plug (male)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	450	0.8	20	NBR	13866523
Plug (male)	1	6.3	1/4"	Internal thread	1/4" NPT	450	0.8	20	NBR	13866524
Plug (male)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	450	1.3	40	NBR	14230106
Plug (male)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	450	1.3	40	NBR	13866553
Plug (male)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	450	1.3	40	NBR	13866555
Plug (male)	2	10	3/8"	Cutting ring connection	8S - M16x1.5	450	1.3	40	NBR	14508725
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	450	1.3	40	NBR	13866551
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	450	1.3	40	NBR	13866554
Plug (male)	2	10	3/8"	Cutting ring connection	10S - M18x1.5	450	1.3	40	NBR	13866556
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	450	1.3	40	NBR	14508729
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	450	1.3	40	NBR	14508728
Plug (male)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	450	1.3	40	NBR	13866557
Plug (male)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	450	1.3	40	NBR	14508730

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Plug (male)	2	10	3/8"	External thread	3/8" BSP cyl.	450	1.3	40	NBR	13866545
Plug (male)	2	10	3/8"	External thread	9/16"-18 UNF [JIC]	450	1.3	40	NBR	14508733
Plug (male)	2	10	3/8"	External thread	11/16"-16 UN [ORFS]	450	1.3	40	NBR	14508734
Plug (male)	2	10	3/8"	Internal thread	1/4" BSP cyl.	450	1.3	40	NBR	13866546
Plug (male)	2	10	3/8"	Internal thread	3/8" BSP cyl.	450	1.3	40	NBR	1019197
Plug (male)	2	10	3/8"	Internal thread	3/8" NPT	450	1.3	40	NBR	13866550
Plug (male)	2	10	3/8"	Internal thread	M 16x1.5	450	1.3	40	NBR	13866549
Plug (male)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	400	3.1	80	NBR	13866592
Plug (male)	3	12.5	1/2"	Cutting ring connection	8L - M14x1.5	400	3.1	80	NBR	13866597
Plug (male)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	400	3.1	80	NBR	13866593
Plug (male)	3	12.5	1/2"	Cutting ring connection	10L - M16x1.5	400	3.1	80	NBR	14230117
Plug (male)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	400	3.1	80	NBR	13866601
Plug (male)	3	12.5	1/2"	Cutting ring connection	10S - M18x1.5	400	3.1	80	NBR	13866605
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	400	3.1	80	NBR	13866594
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	400	3.1	80	NBR	13866598
Plug (male)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	400	3.1	80	NBR	13866602
Plug (male)	3	12.5	1/2"	Cutting ring connection	12S - M20x1.5	400	3.1	80	NBR	13866606
Plug (male)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	400	3.1	80	NBR	13866603
Plug (male)	3	12.5	1/2"	Cutting ring connection	14S - M22x1.5	400	3.1	80	NBR	13866607
Plug (male)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	400	3.1	80	NBR	13866595
Plug (male)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	400	3.1	80	NBR	13866599
Plug (male)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	400	3.1	80	NBR	13866604
Plug (male)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	400	3.1	80	NBR	13866608
Plug (male)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	400	3.1	80	NBR	13866596
Plug (male)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	400	3.1	80	NBR	13866600
Plug (male)	3	12.5	1/2"	External thread	1/2" BSP cyl.	400	3.1	80	NBR	13866588
Plug (male)	3	12.5	1/2"	External thread	3/8" BSP cyl.	400	3.1	80	NBR	13866587
Plug (male)	3	12.5	1/2"	External thread	M 22x1.5	400	3.1	80	NBR	13866589
Plug (male)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	400	3.1	80	NBR	1019199
Plug (male)	3	12.5	1/2"	Internal thread	1/2" NPT	400	3.1	80	NBR	14230119
Plug (male)	3	12.5	1/2"	Internal thread	3/8" BSP cyl.	400	3.1	80	NBR	13866590
Plug (male)	3	12.5	1/2"	Internal thread	M 18x1.5 OR	400	3.1	80	NBR	14230118
Plug (male)	3	12.5	1/2"	Internal thread	M 22x1.5 OR	400	3.1	80	NBR	13866591
Plug (male)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	400	5.6	120	NBR	13866629

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure	Spillage	Max. flow rate	Sealing	Article
		mm				bar	ml	l/min		Max. 200 articles in the table
Plug (male)	4	19	3/4"	Cutting ring connection	12L - M18x1.5	400	5.6	120	NBR	13866633
Plug (male)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	400	5.6	120	NBR	13866630
Plug (male)	4	19	3/4"	Cutting ring connection	15L - M22x1.5	400	5.6	120	NBR	13866634
Plug (male)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	400	5.6	120	NBR	13866636
Plug (male)	4	19	3/4"	Cutting ring connection	16S - M24x1.5	400	5.6	120	NBR	13866638
Plug (male)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	400	5.6	120	NBR	13866631
Plug (male)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	400	5.6	120	NBR	14230121
Plug (male)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	400	5.6	120	NBR	13866637
Plug (male)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	400	5.6	120	NBR	14230122
Plug (male)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	400	5.6	120	NBR	13866632
Plug (male)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	400	5.6	120	NBR	13866635
Plug (male)	4	19	3/4"	Internal thread	1/2" BSP cyl.	400	5.6	120	NBR	13866626
Plug (male)	4	19	3/4"	Internal thread	3/4" BSP cyl.	400	5.6	120	NBR	1032653
Plug (male)	4	19	3/4"	Internal thread	3/4" NPT	400	5.6	120	NBR	13866628
Plug (male)	4	19	3/4"	Internal thread	M 22x1.5	400	5.6	120	NBR	13866627
Plug (male)	6	25	1"	Cutting ring connection	18L - M26x1.5	300	12.3	160	NBR	13866663
Plug (male)	6	25	1"	Cutting ring connection	18L - M26x1.5	300	12.3	160	NBR	13866668
Plug (male)	6	25	1"	Cutting ring connection	20S - M30x2.0	300	12.3	160	NBR	13866671
Plug (male)	6	25	1"	Cutting ring connection	20S - M30x2.0	300	12.3	160	NBR	13866675
Plug (male)	6	25	1"	Cutting ring connection	22L - M30x2.0	300	12.3	160	NBR	13866664
Plug (male)	6	25	1"	Cutting ring connection	22L - M30x2.0	300	12.3	160	NBR	13866669
Plug (male)	6	25	1"	Cutting ring connection	25S - M36x2.0	300	12.3	160	NBR	13866672
Plug (male)	6	25	1"	Cutting ring connection	25S - M36x2.0	300	12.3	160	NBR	13866676
Plug (male)	6	25	1"	Cutting ring connection	28L - M36x2.0	300	12.3	160	NBR	13866665
Plug (male)	6	25	1"	Cutting ring connection	28L - M36x2.0	300	12.3	160	NBR	13866670
Plug (male)	6	25	1"	Cutting ring connection	30S - M42x2.0	300	12.3	160	NBR	13866673
Plug (male)	6	25	1"	Cutting ring connection	30S - M42x2.0	300	12.3	160	NBR	13866677
Plug (male)	6	25	1"	Cutting ring connection	35L - M45x2.0	300	12.3	160	NBR	13866666
Plug (male)	6	25	1"	Cutting ring connection	38S - M52x2.0	300	12.3	160	NBR	13866674
Plug (male)	6	25	1"	Cutting ring connection	38S - M52x2.0	300	12.3	160	NBR	13866678
Plug (male)	6	25	1"	Internal thread	1" BSP cyl.	300	12.3	160	NBR	1019201
Plug (male)	6	25	1"	Internal thread	1" NPT	300	12.3	160	NBR	13866662
Plug (male)	6	25	1"	Internal thread	3/4" BSP cyl.	300	12.3	160	NBR	1019200
Plug (male)	6	25	1"	SAE flange	SAE 6000 psi 1"	300	12.3	160	NBR	14230130

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Plug (male)	6	25	1"	SAE flange	SAE 6000 psi 3/4"	300	12.3	160	NBR	14230129
Plug (male)	6	25	1"	SAE flange	SAE 6000 psi 3/4"	300	12.3	160	NBR	14230128
Plug (male)	8	38	1.1/2"	Cutting ring connection	30S - M42x2.0	350	52.3	220	NBR	13866696
Plug (male)	8	38	1.1/2"	Cutting ring connection	30S - M42x2.0	350	52.3	220	NBR	14230132
Plug (male)	8	38	1.1/2"	Cutting ring connection	38S - M52x2.0	350	52.3	220	NBR	13866697
Plug (male)	8	38	1.1/2"	Cutting ring connection	38S - M52x2.0	350	52.3	220	NBR	13866698
Plug (male)	8	38	1.1/2"	Cutting ring connection	42L - M52x2.0	350	52.3	220	NBR	13866694
Plug (male)	8	38	1.1/2"	Internal thread	1.1/2" BSP cyl.	350	52.3	220	NBR	13866693
Plug (male)	8	38	1.1/2"	Internal thread	1.1/4" BSP cyl.	350	52.3	220	NBR	13866692
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	450	1.3	40	NBR/PTFE	14508714
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	450	1.3	40	NBR/PTFE	13866539
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	450	1.3	40	NBR	14508727

Max. 200 articles in the table

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.