



FLEXION Waterblast hose W484

FLEXION ENDURO™ W484

4 LAYERS OF STEEL WIRE

Light and compact. Reliable and high performance.

Characteristics

Type: W484

Material of inner wall: Water resistant synthetic rubber

Material of outer wall: Synthetic rubber, abrasion, weather and ozon resistant

Quality cover: Flexion Enduro

Temperature range [°C]: -10 / 70 °C

ISO standard: ISO 7751

Application

- Recommended liquids: Water, soap-based water, water-based glycol.

Technical Information

Temperature range:

- -10°C to +70°C

Construction

Tube:

- Water resistant synthetic rubber

Reinforcement:

- Four spiral steel wires

Cover:

- Synthetic rubber, abrasion, weather and ozon resistant

Execution

- Extreme high-pressure cleaning hose
- Meets ISO 7751
- Cover colour: black

Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in	mm	bar	bar	mm		kg/m	
W484-06	DN10	3/8"	20.8	1250	3125	160	Black	0.92	13423177
W484-08	DN12	1/2"	24.2	1200	3000	200	Black	1.19	13423178
W484-12	DN19	3/4"	32	1000	2500	240	Black	1.8	13423179

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.